

SEALING MACHINE M75



GENERAL

This walk-behind machine is developed for sealing trenches with thermoplastic, bitumen-based sealant or mastic asphalt.

One person operation with high sealing capacity.

The 75L boiler is oil-jacketed and has a hydraulic agitator. This makes it possible for the machine to keep the material warm and well agitated for a long time.

With the hydraulic outlet-screw it is possible to control the flow of the thermoplastic to the screed box / application shoe.

The diesel engine and the hydraulic 2-axle front drive make the machine very stable and easy to control.

LPG-burners are heating the boiler and the shoe.

The M75 is CE-approved.

Tailer-made sealing shoe depending on width.

For efficient heating of material for maximum output we recommend a separate boiler.

TECHNICAL SPEC.

Length:	2.130 mm
Width:	1.100 mm
Height:	1.050 mm
Weight:	640 kg, empty
Engine:	Hatz 11hp diesel
Propulsion:	2 wheel drive
Brake:	Hydraulic and mechanical
Boiler:	75L oil-jacketed. 225 C.
Heating:	LPG-burners
Agitator:	Hydraulic
Material screw:	Hydraulic
Temp regulator:	For oil and material (2)
Electrics:	12V
Hydraulic tank:	35L
Hydr. cooler:	Yes
Diesel tank:	20L

**RoadMarking/Maintenance
Equipment of Sweden AB**

www.rme.se

Käglinge v. 33

213 76 Malmö

Sweden

Tel 0046 40 315 880



Manufactured by:

Road Marking/Maintenance Equipment of Sweden AB

www.rme.se

Käglinge v. 33

213 76 Malmö

Sweden

Tel 0046 40 315 880