

## MAXI KOMBI QUATTRO



### GENERAL

Maxi Quattro is a high-capacity machine built on a 4-axle chassis, of which 2 rear axles are friction steered. In that way this machine has a small turning ratio.

This machine is an all-in-one unit meaning that both melting and production are done with this unit. No need for separate preheater truck.

All four preheaters are combined melting- and production units connected to the thermoplastic pump. This makes it possible to find the optimal melting- and melting cycle for high output.

The preheaters are all equipped with loading cells in order to follow and reporting the ongoing consumption of thermoplastic.

There are several different setups; spray, extruder, Flexidot or combined, together with the option of one or two-colour systems.

A crane makes the filling of big bag material into the melting set easier.

The control box allows automatic line system application together with pump control for accurate material flow.

The cab is equipped so that most of the work can be done inside – safe from traffic, noise and exhausts.

### TECHNICAL SPEC.

Length:	10,5 m
Width:	2,55 m
Height:	4,0 m
Weight, tara incl. Truck:	~21.000-21.500 kg
Weight, allowed (EU):	32.000 kg
Melting set:	4x1.200L
Control Box:	RME v2
Extruder:	300-500 mm
Spray block:	2-3 pc /side
Flexidot:	300-450 mm
Bead guns:	2-3 pc/side
Bead tank:	700L
Production pump:	RME 120L/min
Crane:	Palfinger PK4200
Compressor:	Hydraulic
Pointer:	Hydraulic/Pneumatic
Burners:	Riello RG2
Temp regulators:	CAN-BUS