

TRAILER Tr600HO+SPP11d for mastic asphalt and bitumen-based sealant



GENERAL

Special low-built trailer 3.500 kg for bitumen-based sealant and mastic asphalt with volume 600L.

Perfect to fill RME sealing machine M75.

The preheater is oil-jacketed and has a strong hydraulic agitator to handle hard block-materials or powder.

Large filling lid, low and ergonomically placed at the rear.

Heating with oil burner in the preheater's base.

Out-let with manual valve.

Hydraulic hand controls for the preheater to control agitation direction and speed.

Integrated Silent Power Pack (SPP) on the same frame. The engine is silent with noise-proof capsule, which reduces the noise level substantially.

The SPP provides diesel to the burners, hydraulic power to the agitators and electrics for the thermostats etc

This equipment is CE-approved.

TECHNICAL SPEC.

Length:	approx 3,7 m
Width:	1,96 m
Height.:	approx.. 2,4 m
Total weight:	3.500 kg
Tara weight:	approx. 2.000 kg
Preheater volume:	600L
Heating:	Riello oil burner 230V
Indirect heated:	Heating oil
Temp regulators:	For oil and material (2)
Agitation engine:	630cc
Outlet preheater:	Manual valve
Engine:	Hatz 11hp diesel
Silent capsule engine:	Hatz original
Start battery:	Included
Hydraulic pump:	On engine
Oil cooler:	Included
Electrics:	230V-12V incl inverter
Hydraulic tank:	75L
Diesel tank:	75L

**Road Marking/Maintenance
Equipment of Sweden AB**

www.rme.se

Käglinge v. 33

213 76 Malmö

Sweden

Tel 0046 40 315 880